

soft touch



interior vertical surface

Typical application:

furniture, profile wrapping & flat lamination

Décors and colours:

white & black

Width:

~ 1,360 mm

DTS Systemoberflächen GmbH
Arnold-Dammers-Weg 2
D-39291 Möckern

Tel.: +49 (0) 39 221 978 - 0
Fax: +49 (0) 39 221 978 - 97
E-Mail: zentrale@lamine.de
www.lamine.de

witAtone

Exquisit surfaces

With its high-quality, decorative, and haptically appealing design, the WITAtone *soft touch* surface is the perfect finish for interior design. The special acrylic resin lacquer system gives the surface a velvety feel and a look that is almost free of reflections.

Features:



SOFT
TOUCH



ANTI-
FINGERPRINT



HITZE-
BESTÄNDIG

technical data- sheet

WITAtone

* For the adjustments of the surface's quality during the production process, DTS reserves the right to vary the coating grammage. All technical and optical parameters will be fulfilled also with variations in the coating weight or coating thickness. The values are excluding DTS release film. Please refer to the WITAtone storage and handling recommendations.

Textures / Colours	white	black
Grammage / weight gram/m ² (*)	~ 150	~ 150
Scratch resistance DIN EN438-2:1991 EN 438-2:2019	1 N Level 2	1 N Level 2
Abrasion resistance EN 438-2:2019	IP turns ~ 200	IP turns ~ 200
Gloss level at 60° angle	~ 5	~ 5
Chemical resistance EN 438-2:2019	Group 1,3 Level 5 Group 2 Level 3	Group 1, 2, 3 Level 5
Chemical resistance DIN 68861-1:2011	C1	C1
Wrapping radius mm	≥ 3	≥ 3
Carrier foil type	PET	PET
Water stream resistance EN 438-2:2019	Level 5	Level 5
Micro scratch resistance EN 438-2:2019	Class 4	Class 4

All used resins are free of solvent and formaldehyde.

Product composition:

Substrate:	uni-coloured foils
Coating:	transparent EBC lacquers