

# perfect touch



## interior vertical surface

### Typical application:

furniture & flat lamination

### Décors and colours:

black (white upon request)

### Width:

~ 1,360 mm

DTS Systemoberflächen GmbH  
Arnold-Dammers-Weg 2  
D-39291 Möckern

Tel.: +49 (0) 39 221 978 - 0  
Fax: +49 (0) 39 221 978 - 97  
E-Mail: [zentrale@lamine.de](mailto:zentrale@lamine.de)  
[www.lamine.de](http://www.lamine.de)

# witAtone

## Exquisite surfaces

With its high-quality, decorative, and haptically appealing design, the WITAtone *scrambled* surface is the perfect finish for interior design. The special acrylic resin system gives the surface extremely scratch-resistant and durable properties.

## Features:



SCRATCH-  
RESISTANT



ANTI-  
FINGERPRINT



HITZE-  
BESTÄNDIG



EASY TO  
CLEAN

# technical data- sheet

Textures /  
Colours

black

<b>Grammage / weight</b> gram/m <sup>2</sup> (*)	~ 136
<b>Scratch resistance</b> DIN EN438-2:1991 EN 438-2:2019	10 N Level 5
<b>Gloss level</b> at 60° angle	~ 6
<b>Chemical resistance</b> EN 438-2:2019	Group 1, 2, 3 Level 5
<b>Chemical resistance</b> DIN 68861-1:2011	Group 1A, Level 5
<b>Carrier foil type</b>	PET
<b>Water stream resistance</b> EN 438-2:2019	Level 5
<b>Micro scratch resistance</b> EN 438-2:2019	Class 4

All used resins are free of solvent and formaldehyde.

WITAtone

\* For the adjustments of the surface's quality during the production process, DTS reserves the right to vary the coating grammage. All technical and optical parameters will be fulfilled also with variations in the coating weight or coating thickness. The values are excluding DTS release film. Please refer to the WITAtone storage and handling recommendations.

Product composition:

Substrate:	uni-coloured foils
Coating:	transparent EBC resins