

## clean touch

### Tailor-made:

ELESGO clean touch surfaces combine stylish design with a pleasant matt feel and are the perfect choice for modern interiors. Thanks to the innovative EBC technology, they are particularly scratch-resistant, UV-resistant and easy to clean. The integrated anti-fingerprint effect ensures that the surface remains clean and flawless even with daily use - ideal for kitchens, furniture and work areas with high demands on aesthetics and functionality.

### Features:



ANTI-FINGERPRINT



HEAT-RESISTANT



FOOD-SAFE



CHEMICAL-RESISTANT



MICROSCRATCH-RESISTANT

### Typical processing:

Coating for HPL / compact board / CPL, surfaces for direct lamination

### Décors and colours:

Unicolours and print décors, such as wood, stone or fantasy looks

### Colours tolerance:

$\Delta E$ -value  $\leq 1,0$  CIELAB76, measured with d/8° under D65/10° (unicolour)

### Width:

up to 1,600 mm

# technical data sheet

July 2025

DTS Systemoberflächen GmbH  
Arnold-Dammers-Weg 2  
39291 Möckern  
Germany

Phone: +49 (0) 39 221 978 - 0  
Fax: +49 (0) 39 221 978 - 97  
E-Mail: [zentrale@lamine.de](mailto:zentrale@lamine.de)  
[www.lamine.de](http://www.lamine.de)

ON TOP

ELESGO

Texture	clean touch
<b>Grammage</b> g/m² (*)	~ 225
<b>Scratch resistance</b> DIN EN 438-2:1991	up to 6 Newton
<b>Abrasion resistance</b> DIN EN 438-2:2019	IP turns ~ 150
<b>Gloss level</b> 60° angle	2.5 ± 1.5
<b>Chemical resistance</b> DIN EN 438-2:2019	Group 1 level 5 Group 2 level 2 5 (*) Group 3 level 5
<b>Water steam resistance</b> DIN EN 438-2:2019	Level 5
<b>Release film type</b>	PET

Product composition:	
Substrate:	Unicoloured or decoratively printed papers
Impregnation:	Transparent EBC resins
Coating:	Pigmented or transparent EBC resins
Release film:	PET film temperature stable <180° C

\* For the adjustments of surface’s quality during the production process, DTS reserves the right to vary the coating grammage. All technical and optical parameters will be fulfilled also with variations in the coating grammage. The values are excluding DTS release film.

(\*\*) Level 2 for light colours, level 5 for dark colours.

Please refer to the ELES GO HPL storage and handling recommendations.

All used resins are free of solvent and formaldehyde.

Experience it live!  
Scan the QR code  
and see the surface  
in action.



---